

Spitfire EP

E218XM

Wing Span	Wing Area	Flying Weight	Fuselage Length
39.5 in / 1000 mm	257 sq in / 16.6 sq dm	26 oz / 740 g	32.6 in / 830 mm

Requires
4-channel radio w/ 4 micro servos,
20A brushless ESC, Outrunner Motor w/ Propeller Adaptor,
3 cells 11.1V 2100 mAh Li-Po battery & charger



- Scaled park flyer fabricated with top quality balsa/plywood.
- Strong wood structure and tough covering give the airframe the best load to weight ratio and capability for further power upgrades.
- Fully symmetrical airfoil enhance aerobatics performance.
- The Ultralite pilot will greatly enhance scale look without weight penalty.
- All necessary hardware and accessories provided.

COVERINGS CODE NOS. **SGX203/SGX340**
COLOR SCHEMES



E218XM

7MM accessories

Optional Accessories Recommended

<p>Propeller Adaptor</p> <p style="font-size: 8px; color: red;">HW2340100</p>	<p>High Performance Outrunner 28/30</p> <p style="font-size: 8px; color: red;">KM0283010</p>
--	---

⚠ The Following accessories are not included in this package

Max Speed	12,000 rpm
Operating Power	160 W
Operating Voltage	6-12 V
Operating Current	16 A
Peak Current	20 A (max 15 s)
Internal Resistance	95 mΩ
Kv (rpm/V)	1015
Shaft Diameter	3 mm
Length	30 mm

ELECTRIC POWER ⚡

Zero Fighter EP

E216XM

Wing Span	Wing Area	Flying Weight	Fuselage Length
39.5 in / 1000 mm	264 sq in / 17 sq dm	27 oz / 760 g	32 in / 820 mm

Requires

5-channel radio w/ 5 micro servos,
20A Brushless ESC, Outrunner Motor w/ Propeller Adaptor,
3 cells 11.1V 2100mAh Li-Po battery & charger



- Scaled park flyer warbird.
- All wood construction and covered with pre-painted genuine heat shrink LightTex covering.
- Pre-installed retractable landing gear.
- Full house controls.
- Pre-painted fiberglass cowling.
- Ultralite pilot included.



COVERINGS CODE NOS. **SGX216000** **SGX216001** **SGX330**
COLOR SCHEMES



Retractable Landing Gear

E216XM

7MM accessories

Optional Accessories Recommended

<p>Propeller Adaptor</p> <p style="font-size: 8px; color: red;">HW2340100</p>	<p>High Performance Outrunner 28/30</p> <p style="font-size: 8px; color: red;">KM0283010</p>
--	---

⚠ The Following accessories are not included in this package

Max Speed	12,000 rpm
Operating Power	160 W
Operating Voltage	6-12 V
Operating Current	16 A
Peak Current	20 A (max 15 s)
Internal Resistance	95 mΩ
Kv (rpm/V)	1015
Shaft Diameter	3 mm
Length	30 mm

ELECTRIC POWER ⚡